Indoor LED Can Display

A 360-degree indoor advertising display with fine-pitch GOB options, front maintenance and a customizable can-shaped enclosure.



Product rendering. Artwork shown on the screen is illustrative.

Key selection points

- Five indoor configurations from P1.53 to P2
- 500-650 cd/m2 brightness
- 3840 Hz refresh rate
- Front-service flexible LED modules
- Custom graphics, finish and enclosure size

Before requesting a quote

Share the installation location, approximate dimensions, quantity, indoor or outdoor environment, viewing distance, delivery country and target date. Approximate requirements are welcome.

Purchasing terms

MOQ, availability, lead time, warranty, shipping and payment terms are confirmed in the project quotation. This guide does not add a standard commitment.

Technical specifications

Parameter	Published configuration
Pixel pitch options	P2, P2 Plus, P1.875, P1.86 and P1.53
Display sizes	From 305.58 x 520 mm to 764 x 1341 mm
Resolution options	624 x 254 to 1280 x 630 pixels
Module sizes	320 x 160 x 5.2 mm; 300 x 168.75 mm; 302 x 80 mm
Brightness	500-650 cd/m2
Refresh rate / grayscale	3840 Hz / 12-16 bit
Maintenance / protection	Front service; front GOB; rear protection rated IP43
Power / input	400-700 W average / AC 100-240 V
Control system	Novastar or Mooncell
Operating range	-20 to 60 C; 10-85% RH

Configuration and installation note

Published values are model-dependent selection guidance. Confirm dimensions, power, protection, control, installation drawings and destination-specific compliance in the approved quotation. Listed compliance options do not mean every model holds every certificate. This guide is not a fabrication or structural installation drawing.

https://jiamitv.com/product/indoor-led-can-display/

Email: georgejiami@gmail.com | WhatsApp: +86 135 1066 1865

https://jiamitv.com/contact/?product=indoor-led-can-display