LED Ice Can Display

An integrated 360-degree LED display and 50-liter refrigerated can for interactive beverage promotion and mobile retail activation.



Product rendering. Artwork shown on the screen is illustrative.

Key selection points

- Display and refrigeration in one unit
- 50-liter refrigerated capacity
- 0-5 C cooling range
- P1.86 GOB display
- Mobile base with front service

Before requesting a quote

Share the installation location, approximate dimensions, quantity, indoor or outdoor environment, viewing distance, delivery country and target date. Approximate requirements are welcome.

Purchasing terms

MOQ, availability, lead time, warranty, shipping and payment terms are confirmed in the project quotation. This guide does not add a standard commitment.

Technical specifications

Parameter	Published configuration
Pixel pitch	P1.86
Display resolution	1032 x 473 pixels
Display size	Diameter 611 x 1060 mm
Module / module resolution	320 x 160 x 5.2 mm / 172 x 86 pixels
LED / scan	SMD1515 / 1/43 scan
Brightness	500-650 cd/m2
Refresh rate / grayscale	3840 Hz / 12-16 bit
Refrigeration	50 L capacity; 0-5 C; frost-free air cooling
Packaged size / weight	820 x 820 x 1280 mm / 125 kg
Maintenance / protection	Front service; standard GOB; rear IP43
Power / input	500-585 W average / AC 100-240 V
Control system	Novastar or Mooncell

Configuration and installation note

Published values are model-dependent selection guidance. Confirm dimensions, power, protection, control, installation drawings and destination-specific compliance in the approved quotation. Listed compliance options do not mean every model holds every certificate. This guide is not a fabrication or structural installation drawing.

https://jiamitv.com/product/led-ice-can-display/

Email: georgejiami@gmail.com | WhatsApp: +86 135 1066 1865

https://jiamitv.com/contact/?product=led-ice-can-display