LED Reception Counter

A curved GOB LED reception counter combining a professional welcome desk, seamless visual surface and service-friendly modular structure.



Product rendering. Artwork shown on the screen is illustrative.

Key selection points

- Compact X and expanded D models
- P1.8/P1.86 and P2.5 GOB options
- 3840 Hz refresh rate
- Front-maintenance modular design
- Custom content and appearance

Before requesting a quote

Share the installation location, approximate dimensions, quantity, indoor or outdoor environment, viewing distance, delivery country and target date. Approximate requirements are welcome.

Purchasing terms

MOQ, availability, lead time, warranty, shipping and payment terms are confirmed in the project quotation. This guide does not add a standard commitment.

Technical specifications

Parameter	Published configuration
Compact X display	1920 x 960 mm; P2.5 or P1.8 GOB
Compact X resolution	768 x 384 or 1032 x 516 pixels
Compact X overall size / weight	1065 x 1100 x 585 mm / about 97 kg
Expanded D display	2560 x 960 mm; P2.5 or P1.86 GOB
Expanded D resolution	1024 x 384 or 1376 x 516 pixels
Expanded D overall size / weight	1680 x 1068 x 620 mm / about 127 kg
Brightness	500-650 cd/m2
Refresh rate / grayscale	3840 Hz / 12-16 bit
Power	600-700 W compact; 700-950 W expanded
Maintenance / protection	Front service / front IP43 GOB
Control / inputs	Novastar or Mooncell; WiFi, USB and HDMI
Operating range	-20 to 60 C; 10-85% RH

Configuration and installation note

Published values are model-dependent selection guidance. Confirm dimensions, power, protection, control, installation drawings and destination-specific compliance in the approved quotation. Listed compliance options do not mean every model holds every certificate. This guide is not a fabrication or structural installation drawing.

https://jiamitv.com/product/led-reception-counter/

Email: georgejiami@gmail.com | WhatsApp: +86 135 1066 1865

https://jiamitv.com/contact/?product=led-reception-counter