Outdoor LED Can Display

A high-brightness 360-degree outdoor can display engineered for all-weather advertising, front maintenance and long-distance visibility.



Product rendering. Artwork shown on the screen is illustrative.

Key selection points

- P4 and P3.33 outdoor configurations
- 5000-5500 cd/m2 high brightness
- IP65 complete-display protection
- IP68 flexible LED modules
- Front maintenance and custom height support

Before requesting a quote

Share the installation location, approximate dimensions, quantity, indoor or outdoor environment, viewing distance, delivery country and target date. Approximate requirements are welcome.

Purchasing terms

MOQ, availability, lead time, warranty, shipping and payment terms are confirmed in the project quotation. This guide does not add a standard commitment.

Technical specifications

Parameter	Published configuration
Pixel pitch options	P4 and P3.33
Display size - P4	Diameter 1222.3 x H1920 mm
Display size - P3.33	Diameter 916.7 x H1820 mm
Resolution options	688 x 516 pixels; 864 x 504 pixels
Module size	480 x 160 x 15.2 mm
Brightness	5000-5500 cd/m2
Refresh rate / grayscale	3840 Hz / 12-16 bit
Protection	IP65 complete display; IP68 flexible modules
Maintenance	Front service
Power / input	700-3200 W average / AC 100-240 V
Control system	Novastar or Mooncell
Operating range	-20 to 60 C; 10-85% RH

Configuration and installation note

Published values are model-dependent selection guidance. Confirm dimensions, power, protection, control, installation drawings and destination-specific compliance in the approved quotation. Listed compliance options do not mean every model holds every certificate. This guide is not a fabrication or structural installation drawing.

https://jiamitv.com/product/outdoor-led-can-display/

Email: georgejiami@gmail.com | WhatsApp: +86 135 1066 1865

https://jiamitv.com/contact/?product=outdoor-led-can-display